DEC 2 1 2006

U.S. Patent Application No. 10/780,309

Reply to Office Action of September 27, 2006

Docket No.: V9661.0054

## **AMENDMENTS TO THE CLAIMS**

1. (Original) An electrode member, comprising a substrate member and an antimony modified tin dioxide film coating member,

wherein the coating member comprises connected particles from about 3 nm to about 5 nm in size, and

wherein the particles comprise Sn and Sb in a ratio from about 6:1 to about 10:1.

- (Original) The electrode member according to claim 1, wherein the substrate member is made of a material selected from the group consisting of titanium, gold coated titanium and other inert conducting materials.
- (Original) The electrode member according to claim 1, wherein the substrate member is made of titanium.
- 4. (Original) The electrode member according to claim 3, wherein the substrate member is spot-welded with a titanium wire.
- 5. (Currently Amended) An electrode member comprising a substrate member and a coating member, wherein the coating member comprises a tin dioxide modified by antimony, and wherein the coating member comprises connected particles from about 3 nm to about 5 nm in size.
- 6. (Currently Amended) The electrode member according to claim 5, wherein the coating member comprises connected particles of [[less than]] about 5 nm in size.
- 7. (Currently Amended) The electrode member according to claim 6, wherein the connected particles are [[from]] about 3 nm to about 5 nm in size.

**2**008

## U.S. Patent Application No. 10/780,309 Reply to Office Action of September 27, 2006

- Docket No.: V9661.0054
- 8. (Original) The electrode member according to claim 5, wherein the coating member comprises connected particles of Sn and Sb.
- 9. (Currently Amended) The electrode member according to claim 8, wherein the Sn and Sb are in an atomic ratio of [[more]] no less than 6:1.
- 10. (Currently Amended) The electrode member according to claim 8, wherein the Sn and Sb are in an atomic ratio of [[less]] no more than 10:1.
- 11. (Original) The electrode member according to claim 5, wherein the coating member comprises nickel.
- 12. (Currently Amended) The electrode member according to claim 11, wherein the Sb and Ni are in an atomic ratio of [[less]] no more than 10:1.
- 13. (Currently Amended) The electrode member according to claim 11, wherein the Sb and Ni are in an atomic ratio of [[more]] no less than 4:1.

Claims 14-20 (Cancelled).

- 21. (Original) An ozone generation system comprising an electrode according to claim 1 for electrochemical generation of ozone.
- 22. (Original) The ozone generation system according to claim 21, further comprising a solid polymer electrolyte.
- 23. (Currently Amended) The ozone generation system according to claim 22, wherein the solid polymer electrolyte is Nation a sulfonated tetrafluorethylene copolymer.

## U.S. Patent Application No. 10/780,309 Reply to Office Action of September 27, 2006

Docket No.: V9661.0054

Claims 24 -26 (Cancelled).

- 27. (New) The ozone generation system according to claim 21, further comprising an electrolyte selected from the group consisting of HClO<sub>4</sub>, H<sub>2</sub>SO<sub>4</sub>, and H<sub>2</sub>PO<sub>4</sub>.
- 28. (New) The ozone generation system according to claim 21, further comprising an electrolyte having a concentration from about 0.01 M to about 0.5 M.
- 29. (New) The ozone generation system according to claim 21, wherein a constant potential is applied to the electrode member.
- 30. (New) The ozone generation system according to claim 29, wherein the constant potential is in the range from about 1.5V to about 3V.
- 31. (New) The ozone generation system according to claim 30, wherein the constant potential is about 2.2V.
- 32. (New) The ozone generation system according to claim 30, wherein the constant potential is about 2.5V.
- 33. (New) The ozone generation system according to claim 21, further comprising a reference electrode member comprising a Ag/AgCl material.
- 34. (New) The electrode member according to claim 9, wherein the Sn and Sb are in an atomic ratio of no more than 62.5:1.
- 35. (New) The electrode member according to claim 33, wherein the Sn and Sb are in an atomic ratio of about 62.5:1.